

# Z490D4U-2L2T



Intel® Core 10



2933




Micro ATX




10Gbase-T

2 x M.2 (PCIe 3.0 x 4)



### Application

- Cloud Gaming
- HFT Server



		Z490D4U-2L2T
<b>Form Factor</b>		micro ATX (9.6" x 9.6")
<b>Processor System</b>	CPU PCH	Socket LGA1200, supports Intel® 10 <sup>th</sup> Gen. Core™ i9/i7/i5/i3, Pentium, Celeron® Series Processors Intel® Z490
<b>Memory</b>	Capacity	4 DIMM Slots (2DPC); Supports DDR4 ECC/ UDIMMs up to 2933MHz 32GB
<b>Expansion</b>	PCIe slot	1 PCIe 3.0 x16, 1 PCIe 3.0 x8, 1 PCIe 3.0 x1
<b>Storage</b>	M.2 SATA port	2 M-key (PCIe 3.0 x4), supports 22110/2280/2260 and 2280/2260 form factor 6 SATA 6Gb/s (1 support SATA DOM)
<b>Network</b>	RJ45	2 RJ45 (10GbE) by Intel® X710-AT2, 2 RJ45 (1GbE) by Intel® i210
<b>Management</b>	BMC Dedicated IPMI	ASPEED AST2500 : IPMI (Intelligent Platform Management Interface) 2.0 1 RJ45 via Realtek RTL8211E
<b>I/O</b>	USB	2 USB 3.2 Gen 2 Ports: 2 rear Type A 4 USB 3.2 Gen 1 Ports: 2 rear Type A, 2 via header 2 USB 2.0 Ports: 2 via header